



**KILMA-FLEX pipe**

Pipe for underfloor heating system.

High density PE, electronically reticulated, PE-Xc, compliant with standard EN ISO 15875-2. Anti oxygen barrier in EVOH, coextruded, DIN 4726

Code	Roll dim. In m	Pipe dim. In mm	UNITS / pack
464.20.02	240	20 x 2	1
464.20.32	500	20 x 2	1
464.25.02	240	25 x 2.3	1
464.25.22	310	25 x 2.3	1

Do not expose to direct sunlight.

Code	Roll dim. In m	Thickness mm	sqm/pack
778.20.02	2 x 100	0.2	200



**Humidity barrier.**

Roll, sheet in PE to block humidity.



**Base perimetric joint**

Adhesive perimeter joint in expanded PE coupled with LDPE sheet to contain mortar

Code	Supply m	Dim. Mm	Units / pack
475.25.12	60	250 x 8	1



**Corrugated sheet for pipe protection**

Designed to be used also as pipe protection near the manifold

Code	Dimensions mm	Units / pack
483.32.02	ø 32 x 50m	1



Tita-Fix multi-layer pipe in roll. Multilayer pipe in reticulated PE, aluminium, high density PE. Welded aluminium layer.

Code	Dimensions	Roll Length	Units / pack
682.16.00	16 x 2	100m	1
682.16.40	16 x 2	250m	1

Dimensions	Quantity Per Pallet
16 x 2	1100m
20 x 2	1100m

Dimensions: external ø x pipe thickness



Press fitting for multi-layer polyethylene TITA-FIX pipes

Code	Dimensions	Units / pack
224.16.00	16 x 2	10
224.20.00	20 x 2	10

EUROCONUS connection

Dimensions: external ø x pipe thickness




**Polystyrene panel.**

Panel in expanded, smooth fire-resistant polystyrene

Dimensions: 1000 x 1000 mm  
Thickness: 10, 20 and 30 mm  
Density: 30kg/m<sup>3</sup>

Code	Panel Dimensions in mm	Insulating thickness in mm	Units / pack
1189.10.02	1000 x 1000	10	50
1189.20.02	1000 x 1000	20	25
1189.30.02	1000 x 1000	30	16



Panel Supply	
Height mm	Unit dim. Mm
10	1000x1000x500
20	1000x1000x500
30	1000x1000x500



**Net blocking clip**

in plastic material  
with fixing fin.

Interax: 75mm

Height: 28mm

Code	Dimensions mm	Units / pack
825.00.02	75 x 28	100



**Fitting for**

KILMA-FLEX PE pipe

Code	Dimensions	Units / pack
217.17.00	17 x 2	10
217.20.00	20 x 2	10

EUROCONUS connection

Dimensions: external  $\varnothing$  x pipe thickness



**Fixing Clip**

Clip to fix pipes  
to KILMA and Polyunderfoot  
panels. In plastic with locking  
fin.

Code	Dimensions mm	Units / pack
468.45.00	45 x 20	300

Requires a special fixing tool



**Mounting machine**  
for clips.

Easy to use machine  
to quickly fix the clips

Code	Dimensions	Units / pack
469.00.02		1



**Insulated Polymer Manifold Kit**

Code	Size	Outlets	Units / Pack
1005.06.50	1"	5 Way	1
1006.06.50	1"	6 Way	1
1007.06.50	1"	7 Way	1
1008.06.50	1"	8 Way	1
1009.06.50	1"	9 Way	1