

KILMA-FLEX pipe
 Pipe for underfloor heating system.
 High density PE, electronically reticulated, PE-Xc, compliant with standard EN ISO 15875-2. Anti oxygen barrier in EVOH, coextruded, DIN 4726

| Code | Roll dim. In m | Pipe dim. In mm | UNITS / pack |
|-----------|----------------|-----------------|--------------|
| 464.20.02 | 240 | 20 x 2 | 1 |
| 464.20.32 | 500 | 20 x 2 | 1 |
| 464.25.02 | 240 | 25 x 2.3 | 1 |
| 464.25.22 | 310 | 25 x 2.3 | 1 |

Do not expose to direct sunlight.



Humidity barrier.
 Roll, sheet in PE to block humidity.

| Code | Roll dim. In m | Thickness mm | sqm/pack |
|-----------|----------------|--------------|----------|
| 778.20.02 | 2 x 100 | 0.2 | 200 |



Base perimetric joint
 Adhesive perimeter joint in expanded PE coupled with LDPE sheet to contain mortar

| Code | Supply m | Dim. Mm | Units / pack |
|-----------|----------|---------|--------------|
| 475.25.12 | 60 | 250 x 8 | 1 |



Corrugated sheet for pipe protection
 Designed to be used also as pipe protection near the manifold

| Code | Dimensions mm | Units / pack |
|-----------|---------------|--------------|
| 483.32.02 | ø 32 x 50m | 1 |



Tita-Fix multi-layer pipe in roll.
 Multilayer pipe in reticulated PE, aluminium, high density PE. Welded aluminium layer.

| Code | Dimensions | Roll Length | Units / pack |
|-----------|------------|-------------|--------------|
| 682.16.00 | 16 x 2 | 100m | 1 |
| 682.16.40 | 16 x 2 | 250m | 1 |

| Dimensions | Quantity Per Pallet |
|------------|---------------------|
| 16 x 2 | 1100m |
| 20 x 2 | 1100m |

Dimensions: external ø x pipe thickness



Press fitting for multi-layer polyethylene TITA-FIX pipes

| Code | Dimensions | Units / pack |
|-----------|------------|--------------|
| 224.16.00 | 16 x 2 | 10 |
| 224.20.00 | 20 x 2 | 10 |

EUROCONUS connection


Dimensions: external ø x pipe thickness



Polystyrene panel.
 Panel in expanded, smooth fire-resistant polystyrene

Dimensions: 1200 x 800 mm
 Thickness: 30mm
 Density: 30kg/m³

| Code | Panel Dimensions in mm | Insulating thickness in mm | Units / pack |
|------------|------------------------|----------------------------|-----------------------|
| 1189.10.02 | 1200 x 800 | 15 | Currently Unavailable |
| 1189.20.02 | 1200 x 800 | 20 | Currently Unavailable |
| 1189.30.02 | 1200 x 800 | 30 | 40 |



| Panel Supply | |
|--------------|--------------|
| Height mm | Unit dim. Mm |
| 15 | 1200x800x40 |
| 20 | 1200x800x45 |
| 30 | 1200x800x55 |




Net blocking clip

in plastic material
with fixing fin.

Interax: 75mm

Height: 28mm

| Code | Dimensions mm | Units / pack |
|-----------|---------------|--------------|
| 825.00.02 | 75 x 28 | 100 |




Fitting for

KILMA-FLEX PE pipe

| Code | Dimensions | Units / pack |
|-----------|------------|--------------|
| 217.17.00 | 17 x 2 | 10 |
| 217.20.00 | 20 x 2 | 10 |

EUROCONUS connection

Dimensions: external \varnothing x pipe thickness



Fixing Clip

Clip to fix pipes
to KILMA and Polyunderfoot
panels. In plastic with locking
fin.

| Code | Dimensions mm | Units / pack |
|-----------|---------------|--------------|
| 468.45.00 | 45 x 20 | 300 |

Requires a special fixing tool



Mounting machine
for clips.

Easy to use machine
to quickly fix the clips

| Code | Dimensions | Units / pack |
|-----------|------------|--------------|
| 469.00.02 | | 1 |



Insulated Polymer Manifold Kit

| Code | Size | Outlets | Units / Pack |
|------------|------|---------|--------------|
| 1005.06.50 | 1" | 5 Way | 1 |
| 1006.06.50 | 1" | 6 Way | 1 |
| 1007.06.50 | 1" | 7 Way | 1 |
| 1008.06.50 | 1" | 8 Way | 1 |
| 1009.06.50 | 1" | 9 Way | 1 |